

# Pressure Switches

## TOYOTA / VOLKSWAGEN

\*/Cont

### A19-8850

#### TRINARY

Application:  
Landcruiser 100 Series



| LP        | MP        | HP         | THREAD         |
|-----------|-----------|------------|----------------|
| 2.0KG OFF | 15.4KG ON | 32.0KG OFF | Male M11 x 1.0 |

### A19-8846

#### BINARY

Application:  
Toyota



| LP        | HP         | THREAD           |
|-----------|------------|------------------|
| 2.0KG OFF | 32.0KG OFF | Male 3/8"-24 UNF |

### A19-8848

#### BINARY

Application:  
Transporter



| LP        | HP     | THREAD         |
|-----------|--------|----------------|
| 2.0KG OFF | 32.0KG | Male M11 x 1.0 |

### A19-8847

#### TRINARY

Application:  
Golf




| LP        | MP        | HP         | THREAD              |
|-----------|-----------|------------|---------------------|
| 1.5KG OFF | 16.0KG ON | 32.0KG OFF | Female 7/16"-20 UNF |

### A19-8885

#### TRANSDUCER

Application:  
Golf IV  
Lupo Polo



| P1            | P2            | THREAD           |
|---------------|---------------|------------------|
| 1.47V@ 100psi | 2.33V@ 200psi |                  |
| P3            | P4            | THREAD           |
| 3.20V@ 300psi | 4.06V@ 400psi |                  |
|               |               | Male 7/16-20 UNF |

TOYOTA

VOLKSWAGEN